



42SR1

42" LCD SUNLIGHT READABLE WEATHERPROOF LCD

HD
ready

MAIN FEATURES

- Outdoor Sunlight Readable
- W-XGA Resolution (1366 x 768)
- IP66 Rated
- DVI-D (HDCP) HD Ready
- Operating Temperature -20° to + 45°C
- Brightness more than 1000 cd/m2



42SR1 SUNLIGHT READABLE WEATHERPROOF LCD

WEATHERPROOF LCD MONITOR

SANYO has used all of its expertise to create a lightweight aluminium framed LCD monitor, which is protected by anti reflective tempered glass. The newly integrated sun-readable panel is the perfect solution for use outdoors in bright environments. The panels brightness is more than 1000 (cd/m2 for panel) when used in well lit environments.

This means that the SANYO weatherproof monitor can be used in a wide variety of environments due to it being fully approved as weather-resistant, with an IP rating of IP66, and under sunlight. The SANYO weatherproof LCD will make the ideal display for out-door digital signage or in-door public displays.

New product for outdoor applications:

- Bus stops
- Railway lines
- Highways

Indoor applications:

- Shops window
- Restaurant entrances
- Commercial malls

THEFT PROTECTION

The 42SR1 has an Eyebolt on the back of the monitor. This makes tight installation and protects against theft.

RESTRICT ACCESS

The Hotel menu offers a variety of options to help administer control and reduce access.

WARRANTY

The 42SR1 has a 2 year on-site exchange warranty. Please see terms and conditions.

For more information call 0870 787 2696
or visit www.sanyo.co.uk

SPECIFICATIONS

Type	LCD Panel
Screen Size	42"
Aspect Ratio	16:9
Resolution	WXGA 1366 (horizontal) x 768 (vertical) pixels
Brightness	More than 1000 (cd/m2 for panel) With ideal condition under sunlight
Contrast Ratio	1500:1 (typical)
Viewing Angle	178° (Vertical/Horizontal)
Response Time	8ms (gray to gray)
Computer Compatibility	Up to UXGA
Audio Amp	6W + 6W
Colour System	PAL / NTSC3.58(AV-IN) / SECAM
Input Terminals:	
AV1	Video / Audio (Scart) / RGB
AV2	Component (Y,Pb,Pr) RGBHV (BNC x 5) Audio (RCA x 2)
AV3	Video (BNC x1)
Computer 1	RGB (D-Sub 15) Audio (mini-jack)
DVI	DVI-D with HDCP Audio (RCAx2)
RS-232	Serial (D-Sub 9)
Output Terminals:	
AV2	Component (Y,Pr,Pb) RGBHV (BNC x 5) Audio (RCA x 2)
AV3	Video (BNC x1)
RS-232 Serial	Serial (D-Sub 9)
Audio Monitor Output	Audio (RCA x 2)
External Speaker Out	6 W + 6 W
Power Supply	AC 100V - 240V 50-60Hz
Power Consumption	240 W / 2 W Standby
Operation Temperature (with winter mode)	Operation 0-45 °C (32 - 113 °F) Operation -20-45 °C (-4 - 113°F)
Dimensions (WxHxD)	1027 x 620 x 167.5 mm 40.4" x 24.4" x 6.6"
Net Weight	38.5 Kg
Packed Dimensions (WxHxD)	1194 x 273 x 794 mm 41.3" x 25.7" x 6.6"
Packed Weight	42.5 Kg
Included Accessories	Owner's Manual; Remote Control with Batteries; AC Power Cord
IP Rating	IP66 Weather Proof
Optional Accessories	PJ-Net Organizer (POA-LN01)
Safety / EMC	EN60950 2002 EN55022 1998+A2 EN55024 1998+A2 EN61000-3/2-2000 -3/3-1995+A1 2001 UL60950 2002 CAN/CSA-C22.2 FCC part15 Class B, UL Listed 132sets/ 40FT, 154sets/40HC
Vesa Mounts	200 x 200mm

Because our products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.