



## PDG-DHT100L

- Optional WLAN-module enables wireless data transmission of up to 30 m
- Brightness: 6,500 ANSI lumens (2 lamp system), contrast ratio: 7,500 : 1
- Full HD resolution (1,920 x 1,080 pixels) in 16 : 9 format
- 6 interchangeable lenses and 7 adapter boards offer a wide range of possible uses
- Automatic filter exchange for maintenance-free operation up to 30,000 hours
- Strong against dust with new sealed optical engine
- Detailed picture quality for cinemas, large-scale events, digital signage, etc.
- 3 years warranty

## PDG-DHT100L

TECHNICAL DATA	PDG-DHT100L
Category	Professional
Panel	1 x 0.95 " DMD chip (16:9)
Lamp	2 x 330 W UHP (LMP-130)
Brightness	6500 ANSI lumens
Lamp life	2500 h (eco mode) / 2000 h (normal mode)
Fan noise	36 dB (eco mode) / dB (normal mode)
Standard lens	Delivery without lens *
Contrast ratio	7500 : 1
Resolution in pixels	1,920 x 1,080 (HDTV 1,080p)
Image size min. - max. (diagonal):	50 - 600 inch
Uniformity	90 %
Bandwidth/Frequency	230 MHz, Horizontal : 15-120 kHz, Vertical : 48-120 Hz
Colour systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB) Input 1: HDMI (HDCP) Input 1: DVI-D (digital/HDCP) Input 2: Mini DIN 4-pin (S-Video) Input 2: 5x BNC (RGBHV/Composite/Y-Pb/Cb-Pr/Cr) Input 3: freely configurable with optional interface boards Input 4: POA-MD13NET2 (RJ45(LAN)/D-Sub9 pin) Monitor output: D-Sub15 Control Input Jack 1: Mini DIN 8-pin (RS232) Control Input Jack 2: 3.5 mm Stereo Jack (cable remote control) Control Input Jack 3: USB Type B
Keystone correction	vertical +/- 30°, horizontal +/- 30°
Lens shift	1:1 vertical (applies to LNS-LNS-W52), 6.65:-1 - -1:6.65 vertical (applies to LNS-W51/W50/S50/T50/T51), 1:1 horizontal (applies to LNS-W52), 10.7:1 - 1:10.7 horizontal (applies to LNS-W51/W50/S50/T50/T51)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i, 1,080p
Computer compatibility	U-XGA, S-XGA, S-XGA+, W-XGA, XGA, S-VGA, VGA, Mac
Zoom/Focus	depending on lens
Power consumption	W (eco mode) / 923 W (normal mode), 28 W (stand-by mode)
Voltage	100 - 240 V
Warranty	3 years, 90 days lamp warranty (max. 300 hours)
Dimensions (W x H x D)	400.0 x 242.5 x 522.5 mm
Weight (Net)	19 kg
Standard accessories	IR/cable remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Software for Real Colour Manager Pro
Optional accessories	Exchange filter POA-FIL-131, HD wireless transmitter (POA-HDTM01)
Optional adapter boards	DVI-I Board (POA-MD18DVI), 5BNC Board (POA-MD16VD1), HD-SD-SDI Board (POA-MD17SDID), Network Board (POA-MD13NET2), DVI/D-Sub15 Board (POA-MD23ADI), 5-BNC-Board (POA-MD25VD3), HD DATA WIRELESS Receiver board (POA-MD26HDWL)
Lenses	LNS-S50, LNS-T50, LNS-T51, LNS-W50, LNS-W51, LNS-W52

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 01/2009

