



PLC-XU78 | PLC-XU75

- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Brightness: 3,000 ANSI lumens (PLC-XU78) and 2,500 ANSI lumens (PLC-XU75)
- Very quiet: 28 dB in eco mode, (PLC-XU75)
- Key Lock function, Pin Code Lock for security
- Onscreen menu in 16 different languages
- MyLogo Function for custom logo transfer
- Direct Power On/Off lets you switch the projector on/off without delay
- 3 years warranty, 1 year lamp warranty

PLC-XU78 | PLC-XU75

TECHNICAL DATA	PLC-XU78	PLC-XU75
Category	Business & Education	
Panel	3 x 0.63" TFT p-Si (4 : 3), micro lens	
Projection Lamp	220 W UHP (LMP-115)	200 W UHP (LMP-115)
Brightness in ANSI lumens	3,000	2,500
Lamp Life	3,000 h (eco mode)/1,500 h (normal mode)	
Fan Noise	29 dB (eco mode)/34 dB (normal mode)	28 dB (eco mode)/32 dB (normal mode)
Standard lens	F = 1.65–1.81/f = 22.5–27 mm*	
Throw Distance Ratio	1.72–2.07:1*	
Throw Distance	1.4–12.6 m*	
Contrast Ratio	450 : 1	
Resolution in Pixels	1,024 x 768 (XGA)	
Image size min–max (diagonal)	40"–300"	
Uniformity	85 %	
Bandwidth/Frequency	140 MHz, horizontal 15~100 kHz, vertical 50~100 Hz	
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N	
Connections	Input 1: D-Sub15 (RGB/component/SCART-RGB), (component/SCART-RGB with corresponding adapter cable, see "Optional Accessories") Input 2: D-Sub15 (RGB) or Monitor Out Input 3: Cinch (Video) Input 4: Mini DIN 4-pin (S-Video) Audio: 3.5 mm Stereo Jack for Computer, 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (Variable) Control input 1: Mini DIN 8-pin (RS232)	
Audio Function	1 W Mono	
Keystone Correction	vertical +/-20°	
Up/Down Ratio	9 : 1 (Fixed U/D ratio)	
HDTV Compatibility	720p/1035i/1080i (HDTV-compatible)	
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA	
Zoom/Focus	1.2 times/manual	
Power Consumption/Voltage	205 W (eco mode)/290 W (normal mode)/100–240 V	185 W (eco mode)/245 W (normal mode)/100–240 V
Warranty	3 years, 1 year lamp (max. 2,000 h)	
Dimensions (W x H x D)	335 x 79.7 x 238.4 mm	
Weight	3.1 kg	
Standard Accessories	IR remote control, batteries, user manual, D-Sub15 cable, lens cover with cord, power cable, PIN code label	
Optional Accessories	Component/D-Sub15 cable (POA-CA-COMPVGA), SCART/D-Sub15 cable (POA-CA-SCART), remote control with laser pointer (POA-RCKIT03), presentation kit including mouse function (POA-RCKIT04), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)	
Lenses	Standard lens	

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 09/2007

